



Lube & Supplies Inc.

1108 Port Terminal Rd.
Duluth, MN 55802
218-722-2920
800-962-5417
FAX 218-726-0779

13575 Fenway Blvd N
Hugo MN 55038
651-646-0830
800-254-2705
FAX 651-646-0860



**Conventional
Green
50/50 Premixed**

ReX Conventional Green 50/50 pre-diluted antifreeze and coolant is an ethylene glycol based ready to use blend with nitrite-borate buffered inhibitor package that has been the standard conventional coolant over many years.

ReX Conventional Green is compatible with all conventional green coolants and provides year round protection.

Main applications:
Automobiles and light duty trucks.

50/50 Ready to use.
Do not mix with water

ReX Conventional Green is formulated to meet the following specifications and/or recommended practices:

ASTM D-6210	ASTM D-3306
TMC RP-329 Type A	TMC RP-302A
ASTM D-4985	GSA CID A-A-52624

TYPICAL PROPERTIES*

Color.....	Green
Specific Gravity, 68°F	1.046 - 1.078
Reserve Alkalinity	2.0 min
pH	10.2 - 10.8
Freeze Point, °F	-34 max.
Boiling Point, °F	226 min
Foam (m il/sec)	100/3 max
Nitrite (as NaNO ₂) @ 68°F	1015 - 1255 mg/l
Chloride, ppm	25 max
Glassware Corrosion Test	Pass
Water Pump Cavitation Test ...	Pass
Aluminum Corrosion Test	Pass
Simulated Service Test	Pass

NOTE: Typical Properties are current as of the date of publication of this Technical Bulletin. This typical data cannot be guaranteed to be identical to the products produced at any specific time. The data provided in this publication are presented only as a guide to Como Lube & Supplies, Inc. lubricant users.